

CLAIMS

What is claimed is:

1. A system that alters a window assembly to provide the ability to remove
5 traveling window from a motor vehicle window frame, comprising:
a window support system;
a coupling means attached to the window support system;
a motivator adapted to articulate the coupling means, the coupling means
being coupled to the motivator; and
10 a release system coupled to the window support system.
2. The system of claim 1 further comprising a traveling window disposed in the
window support system.
- 15 3. The system of claim 2 further comprising a grasping portion disposed about a
top portion of the traveling window.
4. The system of claim 1 wherein the release system is adapted to snap the
coupling means.

5. The system of claim 1 wherein the release system is adapted to articulate the support member.

5 6. The system of claim 5 wherein the support member comprises a rigid portion and a hinged member coupled to the rigid portion, the hinged portion further coupled to the release system.

7. The system of claim 6 wherein the release system is adapted to articulate the hinged portion substantially away from the traveling window.

10

8. The system of claim 5 wherein the support member comprises a rigid portion and a removable portion coupled to the rigid portion and also coupled to the release system.

15 9. The system of claim 8 wherein the release system is adapted to dislocate the removable portion from the rigid portion sufficiently to allow the traveling window to separate from the window support system.

20

10. A method of enabling a user to automatically dislocate and remove traveling window from a motor vehicle, comprising:

receiving a remote command; and

in response to the remote command dislocating a window assembly from a

5 window actuating system.

11. The method of claim 10 wherein dislocating breaks a linkage.

12. The method of claim 10 wherein dislocating moves a linkage away from a
10 support member.

13. The method of claim 10 wherein the remove command is received electronically.

15 14. The method of claim 10 wherein the remove command is received mechanically.

20

15. A method of enabling a user to dislocate and remove a vehicle window from a motor vehicle window frame comprising:

receiving a remove command; and

in response to the remove command, articulating a support member so that

5 a vehicle window held within the support member in a motor vehicle window frame may be removed from the support member.

16. The method of claim 15 wherein articulating moves a hinged portion of the support member.

10

17. The method of claim 15 wherein articulating breaks away a removable portion of the support member.

18. The method of claim 15 further comprising initiating an actuator to remove
15 the window from the support member.